

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1-55. (canceled)

56. (currently amended) Stopper capsule ~~[[1]]~~ designed as a screw stopper for a container typically designed to contain alcoholic drinks, and ~~typically~~ comprising a bottle in which the neck ~~[[2]]~~ is provided with an outer thread ~~(20)~~ and a tamper-evident ring ~~(21)~~, comprising two parts fixed together in rotation and axially by an assembly means, a) an inner part or insert ~~[[3]]~~ with height h, made of plastic material, comprising ~~a so-called an~~ inner head ~~(30)~~ and ~~a so-called an~~ inner skirt ~~(31)~~, the said inner skirt ~~(31)~~ comprising an inner thread ~~(32)~~ on its inside surface designed to cooperate with the thread ~~(20)~~ of the said neck so as to be able to screw the said capsule to the said neck ~~[[2]]~~ along a rotation axis or an axial direction ~~(10)~~, and b) an outer part or shell ~~[[4]]~~ with height H, ~~typically metallic or metal-based~~, comprising an outer head ~~(40)~~ and an outer skirt ~~(41)~~ masking all or part of the said inner skirt ~~(31)~~ facing it, the said capsule ~~typically~~ being provided with a sealing means ~~[[5]]~~, a tamper-evident means

[[6]] and a first opening means [[7]], and ~~characterised in that wherein:~~

1) the said outer skirt ~~(41)~~ of the said shell [[4]] comprises at least a ~~typically~~ substantially cylindrical part ~~(42)~~ with height H1, diameter D1 adapted to the said neck [[2]], and at least a radially expanded part ~~(43)~~ with height H2, inscribed in a circle with diameter D2 > D1 and forming an annular radial cavity ~~(48)~~, the said ~~typically~~ substantially cylindrical part ~~(42)~~ of the said shell [[4]] radially clamping the said inner skirt ~~(31)~~ of the said insert like a hoop at least facing the said inner thread ~~(32)~~, the said expanded part ~~(43)~~ being ~~designed particularly adapted~~ to facilitate manual gripping of the said capsule [[1]] and rotation of the capsule with respect to the said neck [[2]] to open / close the said container by unscrewing / screwing the said capsule [[1]] on the said neck [[2]],

2) the said radially expanded part ~~(43)~~ and the said ~~typically~~ substantially cylindrical part ~~(42)~~ of the said outer skirt ~~(41)~~ ~~typically have~~ having substantially the same thickness Ep.

57. (currently amended) Capsule according to claim 56 in which the said expanded part ~~(43)~~ ~~typically~~ forms an annular, continuous or discontinuous ring, its upper part ~~typically~~ being

connected to the said outer head ~~(40)~~ or ~~possibly~~ to the said cylindrical part ~~(42)~~, and its lower part being connected to the said cylindrical part ~~(42)~~.

58. (currently amended) Capsule according to claim 56 in which all or part of the said inner skirt ~~(31)~~ of the said insert ~~[[3]]~~ cooperates with all or part of the said ~~typically~~ substantially cylindrical part ~~(42)~~ of the said outer skirt ~~(41)~~, ~~particularly~~ so as to form the said assembly means.

59. (currently amended) Capsule according to claim 56 in which all or part of the said inner head ~~(30)~~ of the said insert ~~[[3]]~~ is facing the said expanded part ~~(43)~~ of the said shell ~~[[4]]~~.

60. (currently amended) Capsule according to claim 56 in which the said height H2 of the said radially expanded part ~~(43)~~ is at least 2 mm ~~and typically varies from 3 to 15 mm~~.

61. (previously presented) Capsule according to claim 56 in which the said diameter D1 varies from 15 mm to 60 mm.

62. (currently amended) Capsule according to claim 56 in which the D2/D1 ratio varies from 1.02 to 1.15 ~~and typically from 1.05 to 1.10~~.

63. (currently amended) Capsule according to claim 56 in which the said ~~typically~~ substantially cylindrical part ~~(42)~~ and the said expanded part ~~(43)~~ are connected by at least one intermediate part with an average slope equal to  $\Delta D/\Delta H$ , where  $\Delta D$  is equal to  $D2 - D1$  and  $\Delta H$  is equal to the height of the said shell ~~[(4)]~~ on which the said diameter varies from  $D1$  to  $D2$ , the said slope ~~typically~~ varying from 0.5 to 2 ~~and preferably from 0.8 to 1.5.~~

64. (currently amended) Capsule according to claim 56 in which the said radially expanded part ~~(43)~~ and the said ~~typically~~ substantially cylindrical part ~~(42)~~ are connected together by a radius of curvature  $R2$  varying from 1.5 mm to  $\Delta D/2$ .

65. (currently amended) Capsule according to claim 56 in which the said expanded part ~~(43)~~ is adjacent to the said outer head ~~(40)~~ in its upper part, and to the said cylindrical part ~~(42)~~ of the said outer skirt ~~(41)~~ in its lower part, the said outer head ~~(40)~~ and the said expanded part ~~(43)~~ being connected by a radius of curvature  $R1$  varying from 1.5 mm to 5 mm.

66. (currently amended) Capsule according to claim 56 in which the upper part and lower part of the said expanded part ~~(43)~~ is adjacent to the said cylindrical part ~~(42)~~ of the said

outer skirt ~~(41)~~, the said expanded skirt ~~(43)~~ being an expanded skirt ~~(43)~~ at a spacing from or offset from the said outer head ~~(40)~~.

67. (currently amended) Capsule according to claim 56 in which the said inner head ~~(30)~~ of the said insert ~~[(3)]~~ is facing all or part of the said expanded part ~~(43, 43)~~, so that the inner thread ~~(32)~~ of the said inner threaded skirt ~~(31)~~ of the said insert ~~[(3)]~~ is facing the said cylindrical part ~~(42)~~ of the said outer skirt ~~(41)~~.

68. (currently amended) Capsule according to claim 56 in which the said inner head ~~(30)~~ of the said insert ~~[(3)]~~ comprises an arch ~~(33)~~ in contact with the said sealing means ~~[(5)]~~ and a recessed spacing means ~~(34)~~ above the said arch, ~~typically~~ formed from spaced concentric rings ~~(340)~~ in contact with the said outer head ~~(40)~~.

69. (currently amended) Capsule according to claim 56 in which when the said capsule ~~[(1)]~~ seals the said neck ~~[(2)]~~ by screwing, the axial height of the said expanded part ~~(43)~~ is such that it is above the said outer thread ~~(20)~~ of the said neck ~~[(2)]~~ and ~~possibly~~ above the said locking ring ~~(22)~~ of the said neck ~~[(2)]~~.

70. (currently amended) Capsule according to claim 56 in which the thickness of the said inner skirt ~~(31)~~ of the said insert ~~[(3)]~~ at the bottom of the groove varies between 0.1 mm and 0.5 mm.

71. (currently amended) Capsule according to claim 56 in which the said insert ~~[(3)]~~ is an insert ~~(31)~~ for which the inner skirt ~~(31)~~ is ~~said to be "short"~~ short, the said insert having a height h1 ~~typically~~ varying from 6 mm to 20 mm, the said height h1 ~~typically~~ corresponding to the height of the said neck from the said locking ring ~~(22)~~ as far as the bottom of the said outer thread ~~(21)~~.

72. (currently amended) Capsule according to claim 71 in which the ratio H/h1 may vary from 1.1 to 4 ~~and preferably from 2 to 3~~.

73. (currently amended) Capsule according to claim 56 in which the said outer skirt ~~(41)~~ includes the said tamper-evident means ~~[(6)]~~, the said outer skirt ~~(41)~~ being capable of forming a crimped zone ~~(60)~~ under the said tamper-evident ring ~~(21)~~, and the said first opening means ~~[(7)]~~, the said outer skirt ~~(41)~~ comprising a line of weakness ~~(70)~~ fixing a guarantee strip ~~(71)~~ above the said line of weakness by narrow connecting strips, and capable of forming the said crimped zone.

74. (currently amended) Capsule according to claim 56 in which the said insert  $[(3)]$  is an insert ~~(3")~~ for which the inner skirt ~~(31)~~ is ~~said to be "long"~~ long, the said insert having a height  $h_2$  ~~typically~~ varying from 20 mm to 50 mm, the said height  $h_2$  ~~typically~~ corresponding to the height of the said neck from the said locking ring ~~(22)~~ as far as the bottom of the said tamper-evident ring ~~(21)~~ of the said neck  $[(2)]$ , the ratio  $H/h_2$  ~~typically~~ varying from 0.8 to 1.1.

75. (currently amended) Capsule according to claim 56 in which the said insert  $[(3)]$  is an insert ~~(3")~~ in which the inner skirt ~~(31)~~ is ~~said to be "very long"~~ very long, the said neck comprising a lower tamper-evident ring ~~(21')~~, the said insert having a height  $h_3$  more than 50 mm, the said height  $h_3$  ~~typically~~ corresponding to the height of the said neck from the said locking ring ~~(22)~~ as far as the bottom of the said lower tamper-evident ring ~~(21')~~, the ratio  $H/h_2$  ~~typically~~ varying from 0.8 to 1.1.

76. (currently amended) Capsule according to claim 74 in which the said inner skirt ~~(31)~~ includes the said tamper-evident means  $[(6)]$  and the said first opening means  $[(7)]$ , the said inner skirt ~~(31)~~ comprising a guarantee strip ~~(71)~~ in its lower part connected by a line of weakness ~~(70)~~ provided with several

narrow connecting strips, the said guarantee strip ~~(71)~~ cooperating with the said tamper evident ring ~~(21)~~ by means of attachment tabs ~~(61)~~, so that the said tamper-evident ring ~~(21)~~ blocks the said tabs ~~(61)~~ and the said guarantee strip ~~(71)~~ in the axial direction, and thus first opening of the said capsule causes a visible rupture of the said narrow connecting strips along the said line of weakness ~~(70)~~.

77. (currently amended) Capsule according to claim 74 in which the said guarantee strip ~~(71)~~ comprises an outer projection ~~(62)~~ forming a rim for the said outer skirt, ~~typically comprising~~ comprising a stop rim with a width varying from 0.5 to 5 times the thickness  $E_p$  of the said outer skirt ~~(41)~~.

78. (currently amended) Capsule according to claim 76 in which the said attachment tabs ~~(61)~~ are connected to the said guarantee strip ~~(71)~~ or ~~possibly~~ to the said outer projection ~~(62)~~.

79. (currently amended) Capsule according to claim 78 in which each of the said attachment tabs ~~(61)~~ is fixed to the said guarantee strip ~~(71)~~ or to the said projection ~~(62)~~ by a thinned part ~~(610)~~ of the said tab ~~(61)~~ making it flexible.

80. (currently amended) Capsule according to claim 76 in which the said line of weakness ~~(70)~~ is a notched line ~~(70')~~ so as to avoid any unwanted breakage of the narrow connecting strips, ~~particularly~~ during the said sealing or capping of the said container.

81. (currently amended) Capsule according to ~~claims~~ claim 56 in which the said expanded part ~~(43)~~ has a profile ~~typically~~ forming a circle or a regular polygon, ~~typically~~ with N sides where N varies from 5 to 18 ~~and preferably from 6 to 12 sides,~~ over all or part of its height H2.

82. (currently amended) Capsule according to claim 56 in which the said outer skirt ~~(41)~~ forms a surface of revolution over all or part of its height H, with a constant or variable radius depending on the height considered, or has a symmetry of rotation with angle  $360^\circ/N$  where H varies from 4 to 80, the said outer skirt ~~(41)~~ ~~typically~~ forming a plurality of N notches so as to facilitate manual gripping and rotation of the said capsule.

83. (currently amended) Capsule according to claim 56 in which the said assembly means fixing the said inner part ~~[(3)]~~ and outer part ~~[(4)]~~ in rotation and axially comprises a mechanical or chemical anchor means, ~~typically~~ by gluing the said inner part ~~[(3)]~~ and outer part ~~[(4)]~~.

84. (currently amended) Capsule according to claim 83 in which the said inner skirt ~~(31)~~ cooperates with the said cylindrical part ~~(42)~~ facing it, over all or part of the said height h, due to an adhesive layer fixing the said inner skirt ~~(31)~~ and the said cylindrical part ~~(42)~~.

85. (currently amended) Capsule according to claim 56 in which the said outer part or shell ~~[(4)]~~ is made of ~~aluminium~~ aluminum, tin or a metalloplastic multi-layer material with a deformation under stress similar to the deformation of ~~aluminium~~ aluminum or tin.

86. (currently amended) Capsule according to claim 85 in which the said outer part ~~[(4)]~~ is made of ~~aluminium~~ aluminum treated on the surface, ~~typically~~ brushed or anodised, to create a "~~metallic~~" metallic appearance or ~~colour~~ color.

87. (currently amended) Capsule according to claim 56 in which the said inner part ~~(3)~~ ~~may be~~ is an insert ~~moulded~~ molded from a thermoplastic material, ~~typically~~ PE, PP, PET, SEBS or PS, ~~possibly~~ comprising one or several mineral fillers ~~and typically~~ tale.

88. (currently amended) Capsule according to claim 56 in which the said sealing means ~~(5) typically~~ comprises an add-on seal ~~(50)~~ or a sealing insert ~~(51)~~, or ~~possibly~~ a circular sealing lip.

89. (currently amended) Capsule according to claim 88 in which the said sealing means ~~[(5)]~~ comprises the said add-on seal ~~(50)~~ with a sufficiently large diameter to at least cover the locking ring ~~(22)~~ of the neck ~~[(2)]~~ and a compression means, carried by the inner surface of the said insert, to apply the said seal ~~(50)~~ to seal the said neck ~~[(2)]~~ during the said capping and ~~typically~~ on the locking ring ~~(22)~~ of the said neck ~~[(2)]~~.

90. (currently amended) Capsule according to claim 89 in which the said compression means is composed of or comprises an axial compression means, the said axial compression means ~~typically~~ comprising a rib or an annular overthickness ~~(300)~~ formed on the inner wall of the said inner head ~~(30)~~ or the said inner skirt ~~(31)~~, and designed to compress the said add-on seal ~~(50)~~ along the said axial direction ~~(10)~~ on the upper part ~~(220)~~ of the said locking ring ~~(22)~~, ~~part typically plane or inclined by up to 45°.~~

91. (currently amended) Capsule according to claim 89 in which the said compression means comprises a radial compression means, the add-on seal ~~(50)~~ being compressed onto the said neck along a radial direction ~~(11)~~ due to the said annular tab ~~(311)~~, the said radial direction ~~(11)~~ forming an angle of at least 45° with the said axial direction ~~(10)~~.

92. (currently amended) Capsule according to claim 91 in which the said radial compression means comprises an annular overthickness ~~(300)~~ typically formed at the junction between the said inner head ~~(30)~~ and the said inner skirt ~~(31)~~, and designed to compress the said seal ~~(50)~~ over all or part of the striated part ~~(220)~~ and / or on the typically a vertical part of the locking ring ~~(22)~~.

93. (currently amended) Capsule according to claim 92 in which the said annular overthickness ~~(300)~~ is in the form of a step formed at the inner junction of the inner head ~~(30)~~ and the inner skirt ~~(31)~~ so as to compress the said seal ~~(50)~~ in the radial direction.

94. (currently amended) Capsule according to claim 91 in which the said radial compression means comprises a chamfer ~~(301)~~ of the said insert ~~[(3)]~~ at the inner junction of the inner head ~~(30)~~ and the inner skirt ~~(31)~~, the said chamfer ~~(301)~~ having

a curvature ~~typically~~ similar to that of the striated part ~~(220)~~ of the said locking ring ~~(22)~~ facing it.

95. (currently amended) Capsule according to claim 89 in which the thickness  $E_j$  of the seal, ~~typically between 0.5 and 2.5 mm,~~ is chosen ~~particularly~~ as a function of the radial space  $E_o$  between the said neck and the said capsule, such that the said container is capped and sealed by the said capsule, the thickness of the locally compressed seal or the distance  $E$  between the end of the said compression means and the said locking ring then ~~typically~~ being between  $0.3 \times E_j$  and  $0.7 \times E_j$ , where  $E_j$ .

96. (currently amended) Capsule according to claim 91 in which the said radial compression means comprises an annular tab ~~(311)~~ formed on the inner wall of the said inner skirt ~~(31)~~ of the insert  $[(3)]$ .

97. (currently amended) Capsule according to claim 89 in which the said compression means comprises an axial compression means and a radial compression means, the said axial and / or radial compression means forming an integral part of the said insert  $[(3)]$  or forming an add-on part.

98. (currently amended) Capsule according to claim 88 in which the said inner skirt ~~(31)~~ comprises a rib or a plurality of

holding pins ~~(310)~~ capable of fixing the said add-on seal ~~(50)~~ to the said insert ~~[(3)]~~.

99. (currently amended) Capsule according to claim 56 in which a spout ~~(8)~~ and / or a so-called "anti-fill" an anti-fill device ~~(8')~~ is fixed reversibly to the said insert ~~[(3)]~~ or possibly to the said sealing means ~~(5, 50, 51)~~, typically due to an inner ring ~~(35)~~ of the said insert ~~[(3)]~~ temporarily cooperating with a peripheral skirt of the said spout ~~[(8)]~~ and / or the said anti-fill device ~~(8')~~.

100. (currently amended) Capsule according to claim 56 in which the said insert ~~[(3)]~~ comprises an axial snap-on means, typically in the form of a plurality of flexible annular tabs ~~(302)~~ cooperating with the said radially expanded part ~~(43)~~ so as to fix the said insert ~~[(3)]~~ into the said shell ~~[(4)]~~ along the axial direction and so as to further increase the shock resistance of the said expanded part ~~(43)~~ of the said shell ~~[(4)]~~.

101. (currently amended) Capsule according to claim 56 in which the said annular radial cavity ~~(48)~~ is filled with a material ~~(49)~~, typically an adhesive material, so as to simultaneously fix the insert to the said shell and to obtain a very high shock resistance for the said expanded part ~~(43)~~.

102. (currently amended) Capsule according to claim 56 in which the said radially expanded part ~~(43)~~ has a non-circular section in a plane perpendicular to the said axial direction ~~(10)~~ so as to facilitate gripping and manual rotation of the said capsule ~~[(1)]~~.

103. (currently amended) Stopper capsule ~~[(1)]~~ designed for screw capping of a container typically designed to contain alcoholic drinks, ~~typically~~ comprising a bottle with a neck ~~[(2)]~~ provided with an outer screwing thread ~~(20)~~ and a tamper-evident ring ~~(21)~~, comprising an outer part or shell ~~[(4)]~~ with height H, ~~typically~~ that is metallic or metal based, comprising an outer head ~~(40)~~ and an outer skirt ~~(41)~~ concealing all or part of the said inner skirt ~~(31)~~ facing it, the said capsule being provided with a sealing means ~~[(5)]~~, a tamper-evident means ~~[(6)]~~ and a first opening means ~~[(7)]~~, and ~~characterised in that wherein~~ the said outer skirt ~~(41)~~ of the said shell ~~[(4)]~~ comprises at least a ~~typically~~ substantially cylindrical part ~~(42)~~ with height H1, diameter D1 adapted to the said neck ~~[(2)]~~, and at least one radially expanded part ~~(43)~~ with height H2, inscribed in a circle with diameter  $D2 > D1$  and forming an annular radial cavity ~~(48)~~, the said expanded part ~~(43)~~ being ~~designed particularly adapted~~ to facilitate manual gripping of the said capsule ~~[(1)]~~ and rotation of the capsule with respect

to the said neck ~~[(2)]~~ to open / close the said container by unscrewing / screwing the said capsule ~~[(1)]~~ on the said neck ~~[(2)]~~, and ~~in that wherein~~ the said radially expanded part ~~(43)~~ and the said ~~typically~~ substantially cylindrical part ~~(42)~~ of the said outer skirt ~~(41)~~ have the same thickness  $E_p$ .

104. (currently amended) Method for manufacturing capsules ~~[(1)]~~ according to claim 56 in which:

a) the said inner part or insert ~~[(3)]~~ is ~~possibly~~ procured, ~~possibly~~ including the said add-on seal, and ~~possibly~~ the said spout or the ~~"anti-fill"~~ anti-fill device ~~(8, 8')~~,

b) a blank ~~(4')~~ of the said outer part ~~[(4)]~~ is formed, the said blank ~~(4')~~ comprising a skirt ~~(41')~~ with diameter  $D_1$  and height  $H' > H$ , ~~typically by drawing, extrusion or spinning,~~ starting from a ~~typically~~ metallic strip material,

c) the said blank ~~(4')~~ is transformed into the said outer part ~~[(4)]~~ by making a local radial expansion of the said outer skirt ~~(41')~~ over the said height  $H_2$ , such that the said radially expanded part ~~(43)~~ and the said ~~typically~~ substantially cylindrical part ~~(42)~~ of the said outer skirt ~~(41)~~ have the same thickness  $E_p$ ,

d) the said add-on seal ~~(50)~~ and / or the said inner part ~~[(3)]~~ is ~~/are possibly~~ assembled to the said outer part ~~[(4)]~~, ~~typically by deposition of an adhesive onto the said cylindrical part (42) or between it and the said outer skirt~~

~~(41)~~, and then force fitting the said inner part ~~(31)~~ into the said outer part ~~(41)~~.

105. (currently amended) Method according to claim 104 in which, in step c, the said local radial expansion is obtained by axial compression of an expandable punch ~~(95)~~ in the said blank ~~(41)~~ placed in a shaping die ~~(91, 91')~~ forming a radial cavity ~~(92)~~ with a profile similar to the profile of the said expanded part ~~(43)~~, the said expandable punch ~~(95)~~ forcing a part of the said outer skirt ~~(41')~~ radially into contact with the said inner wall of the said radial cavity ~~(92)~~, due to the said axial compression, ~~typically~~ obtained by axial displacement of a slide ~~(96)~~.

106. (currently amended) Method according to claim 105 in which the said local radial expansion is an expansion progressively extending in the axial direction, the said expandable punch starting to apply its action at the bottom part ~~(45)~~ of the said blank ~~(41)~~ closest to the said outer head ~~(40)~~, then progressively continuing to exert its action by moving away from the said outer head ~~(40)~~, so as to enable free creep of the said outer skirt ~~(41')~~ in the said cavity ~~(92)~~, the said free creep being made possible by progressive blocking of the said skirt ~~(41')~~ from the said outer head ~~(40)~~, the remainder of the said skirt ~~(41')~~ not being blocked in contact with the said die

~~(91')~~ by the said expandable punch ~~(95)~~, so as to progressively form the said expanded part ~~(43)~~ in the axial direction without any risk of metal breakage.

107. (currently amended) Method according to claim 106 in which the said expandable punch ~~(95)~~ has an axial profile ~~(950)~~ adapted to obtaining the said progressive expansion by radial compression.

108. (currently amended) Method according to claim 105 in which the said expandable punch is formed from an elastomer material capable of deforming under the said radial compression, the said elastomer material having a Shore hardness chosen as a function of the mechanical characteristics of the said material from which the said blank ~~(4')~~ is made, ~~typically metallic~~, the said hardness being greater than a given value depending on the mechanical characteristics and the thickness of the said material forming the said skirt ~~(41')~~, such that the said axial compression develops a radial force of the said elastomer material greater than the local resistance of the said skirt ~~(41')~~ to deformation by radial expansion.

109. (currently amended) Method according to claim 105 in which the said slide ~~(96)~~ is metallic or made from an elastomer with hardness greater than the hardness of the expandable punch

~~{95}~~, or it comprises an elastomer or rubber lower part ~~{96'}~~ with a Shore A hardness greater than the hardness of the said expandable punch ~~{95}~~.

110. (currently amended) Method according to claim 105 in which the said slide ~~{96}~~ has a shoulder ~~{960}~~ with a width equal to at least the said thickness  $E_p$ , so that the said shoulder can apply an axial compression on the end of the said outer skirt ~~{41}~~ when the said slide ~~{96}~~ is at its bottom dead ~~centre~~ center, and thus facilitate the said expanded part ~~{43}~~ being forced into contact with the wall of the said cavity ~~{92}~~.